

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/082744 A1

(51) International Patent Classification: **B65D 83/14,**
F16K 17/06

[GB/NL]; Grote Straat 26, NL-5151 JE Drunen (NL).
VAN SWIETEN, Roy [NL/NL]; Stationsweg 4, NL-5321
NH Hedel (NL).

(21) International Application Number:
PCT/IB2004/002522

(74) Agent: SPIERENBURG, Pieter; Spierenburg & Partner
AG, Patent- und Markenanwälte, Mellingerstrasse 12,
CH-5443 Niederrohrdorf (CH).

(22) International Filing Date: 5 August 2004 (05.08.2004)

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AI, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(26) Publication Language: English

(30) Priority Data:
04405059.9 30 January 2004 (30.01.2004) EP

(71) Applicant (for all designated States except US): KELTUB
B.V. [NL/NL]; Wolput Postbus 28, NL-5250 AA Vlijmen
(NL).


(72) Inventors; and

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

(75) Inventors/Applicants (for US only): REGAN, Phil

[Continued on next page]

(54) Title: PRESSURE CONTROL DEVICE



(57) Abstract: The present invention concerns a pressure control system with a pressure control device (1) for maintaining a constant predetermined excess pressure arranged in a fluid dispensing container (50; 60). The pressure control device comprises a first cylinder (15), a piston (13) movable within said first cylinder filled with a gas exerting said predetermined excess pressure, a second chamber (7), a passageway from the second chamber (7) to the outside of the device leading to the container (50; 60), a valve (18, 23) for releasing and closing said passageway. The second chamber is substantially a second cylinder (2) with a closed end (34) and an open end provided with a rim part (4), on which a closure (5) is mounted to close the second chamber, such that the second chamber is encompassing the first chamber, wherein the first chamber is part of the closure.

WO 2005/082744 A1

